

FACILITIES GUIDE



THE VENETIAN[®] RESORT
LAS VEGAS

ELEVATORS	3-4
FLOOR LOAD LIMITS	5
ROOM SPECIFICATIONS	5
FOYERS	5
THE CONVENTION CENTER SECURITY	5
EXHIBIT HALL LIGHTING	6
LEVEL 1/GROUND LEVEL	6-8
LEVEL 2/CASINO LEVEL AND THE CONVENTION CENTER	9-13
LEVEL 3/GRAND CANAL SHOPPES® LEVEL	14-15
LEVEL 4	16-17
LEVEL 5	18
POOL DECKS	19

TABLE OF CONTENTS

Elevators

Freight Elevator to Halls B & C

When The Venetian Expo Las Vegas front lobby freight elevator is needed, it must be included as part of an event's execution plan for move-in, show days, and/or move-out operations. Show Management must contact the Expo Event Manager to obtain permission for their contracted security to be posted and operate the elevator. Please expect delays in coordinating short notice pop-up requests, as this creates an unexpected task for the contracted security company. Once permission is granted, contracted security is responsible for checking in/out at The Venetian Expo Security podium to receive Saltos access controls.

Location & Access: From The Venetian Expo Lower Lobby or Upper Lobby into Hall B or Hall C

Elevator Number: Z71189-FRNT FRT ELV
Size: 7'5" (L) x 5'5" (W) x 8' (H)
Capacity: 10,000 lbs.

Available to in-house personnel and authorized set-up crews.

Freight Elevator(s) to Hall D and The Venetian Ballroom

These elevators are for the use of "The Venetian Convention & Expo Center" Team Members and our Tenants. Should you or your production company need access to these elevators, usage must be arranged through your Conference Manager.

Location & Access: From Sub Hall D to Hall D/The Venetian Ballroom Level

Elevator Number: ENGS-1 (1 Elevator)
Size: 20'6" (L) x 10' (W) x 12' (H)
Capacity: 20,000 lbs.

Elevator Number: ENGS-2 (1 Elevator)
Size: 12'6" (L) x 10' (W) x 12' (H)
Capacity: 10,000 lbs.

Available to in-house personnel and authorized set-up crews.

Service Elevator(s) near The Venetian Ballroom A

These elevators are for the use of "The Venetian Convention & Expo Center" Team Members. Should you or your production company need access to these elevators, usage must be arranged through your Catering & Conference Manager.

Location & Access: From Receiving Docks to The Venetian Ballroom Level

Elevator Number: LSLS-3 & LSLS-4 (2 Elevators)
Size: 8'4" (L) x 6' (W) x 9'2" (H)
Capacity: 5,000 lbs.

Elevator Number: LSLS-1 & LSLS-2 (2 Elevators)
Size: 8'4" (L) x 6' (W) x 9'2" (H)
Capacity: 5,000 lbs.

Available to in-house personnel and authorized set-up crews.

Service Elevator to Hall C

This elevator is for the use of "The Venetian Convention & Expo Center" Team Members. Should you, your general contractor or production company need access, please make arrangements through your Expo Event Manager.

Location & Access: From The Venetian Expo back of house warehouse to south end of Hall C.

Elevator Number: Z71191-REAR FRT ELV
Size: 15' (L) 12' x (W) x 7'10" (H)
Capacity: 20,000 lbs.

Available to in-house personnel and authorized set-up crews.

Facilities Guide

Service Elevator(s) to Levels 2, 3, 4, and 5

These elevators are for the use of "The Venetian Convention & Expo Center" Team Members. Should you or your production company need access to these elevators, usage must be arranged through your Conference Manager. These service elevators are located near the receiving docks across from the bus transportation area on Level 1 of The Convention Center.

Elevator Number: PS-1, PS-2, PS-3, and PS-4 (4 Elevators)
Size: 12' (L) x 5'4" (W) x 9'2" (H)
Capacity: 10,000 lbs.

Freight Elevator(s) to Level 2, 3, 4, and 5

Located across from the bus transportation area, the freight elevators provide access from ground level to levels 2, 3, 4, and 5.

Elevator Number: MEL8 & MEL9
Size: 20' (L) x 12' (W) x 9' (H)
Capacity: 20,000 lbs.

Available to in-house personnel and authorized set-up crews.

Guest Floor Elevators

These elevators are for the use of Resort Guests and are not designed for the transfer of production equipment or exhibit freight.

Location & Access: Access to The Venetian Guest Suite Tower

Elevator Numbers: TSBBP-1 through TSBBP-22
Size: 6' 9 3/4" (W) x 6' 3/4" (L)
Capacity: 3,500 lbs.

Location & Access: Access to Venezia Guest Suite Tower

Elevator Numbers: P1-P15, G7, and G8
Size: 6' 8" (W) x 5' 5" (L)
Capacity: 3,500 lbs.

Location & Access: Access to The Palazzo Guest Suite Tower

Elevator Numbers: T13-T36
Size: 6' 7" (W) x 5' 4" (L)
Capacity: 3,500 lbs.

Freight Elevator(s) to the Pool Deck

These elevators are for the use of "The Venetian Convention & Expo Center" Team Members.

Location & Access: From Ground Level to The Venetian and The Palazzo Pool Decks

Elevator Numbers: LSSS-1, LSSS-2 (2 Elevators)
Size: 5'8" (W) x 8'6" (L) x 10' (H)
Capacity: 5,000 lbs.

Elevator Number: LSSS-3 (1 Elevator)
Size: 7'8" (W) x 9'4" (L) x 10' (H)
Capacity: 8,000 lbs.

Available to in-house personnel and authorized set up crews.

FLOOR LOAD LIMITS

In Halls A, B, C, and D floor load limits are 250 lbs. per square foot, static weight.

In Hall G there is no limit.

In The Venetian Ballroom, Level 2, Level 3, Level 4, and The Palazzo Ballroom floor load limits are 150 lbs. per square foot, static weight.

For The Venetian pool deck and The Palazzo pool deck floor load limits are 100 lbs., static weight.

ROOM SPECIFICATIONS

Visit venetianlasvegas.com/meetings for additional information regarding room specifications.

FOYERS

All foyer space in "The Venetian Convention & Expo Center" is considered public space. No guaranteed private use and/or access should be expected at any time, without prior arrangement and written approval. Electric carts, scooters, or lifts of any kind are prohibited in the hallways without visqueen protecting the carpet. Pallet jacks are prohibited at all times.

THE CONVENTION CENTER SECURITY

Note that most meeting rooms are joined by airwall doors that cannot be secured by lock and key. If you have items of value in these rooms, we strongly advise security coverage. "The Venetian Convention & Expo Center" is not responsible for lost or damaged items left in the meeting room(s).

EXHIBIT HALL LIGHTING

On move-in and move-out days, Halls A-D and G provide 50% lighting at no charge. On the final move-in day a light check will occur at 100% and any lights needing replacement will be changed out. Once completed the lights will return to 50%.

On show days during operating hours, 100% lighting is provided. If additional lighting during non-show hours is needed, please contact your Expo Event Manager for a fee schedule. Any overhead lights that burn out during show hours will be replaced that day at the close of show.

LEVEL 1 (GROUND LEVEL)

The Venetian Expo Meeting Rooms 101-103 and 201-203

One (1) section divides by airwalls into six (6) rooms- 101-103 and 201-203

Dimensions: 29' (W) x 44' (L)

Chandeliers: Not applicable

Ceiling Height: 13'3" at lowest point; 14'6" at highest point

Power: (1) 20 AMP 120 volts 1 phase

(1) 60 AMP 208 volts 3 phase outlet inside entrance of room

(1) 20 120 volts 1 phase outlet in floor pocket at rear of room

Located in each divisible room:

A/V Panel Lighting Controls Outlets

At the A/V Panels of Each Room

- (1) RGB Port
- (1) Horizontal/Vertical Port
- (1) Cable TV Port
- (2) Fiber Ports
- (2) Line in Ports
- (2) Mic Lines
- (4) CAT 5 Ports
- (4) Phone Ports

The Venetian Expo Meeting Rooms 301-310

Two (2) sections with each dividing by airwalls into five rooms- 301-305 and 306-310

Dimensions: 29' (W) x 43' (L) - Rooms 301-304 and 306-309
27' (W) x 43' (L) - Rooms 305 and 310

Chandeliers: Not applicable

Ceiling Height: 13'3" at lowest point, 14'6" at highest point

Power: (1) 20 AMP 120 volts 1 phase

(1) 60 AMP 208 volts 3 phase outlet inside entrance of room

Located in each divisible room:

A/V Panel Lighting Controls Outlets

At the A/V Panels of Each Room

- (1) RGB Port
- (1) Horizontal/Vertical Port
- (1) Cable TV Port
- (2) Fiber Ports
- (2) Line in Ports
- (2) Mic Lines
- (4) CAT 5 Ports
- (4) Phone Ports

Facilities Guide

The Venetian Expo Meeting Rooms 401-407

Two (2) sections: Rooms 401-404 divides by airwalls into four rooms

Rooms 405-407 divides by airwalls into three rooms

Dimensions: 29' (W) x 49' (L) - Rooms 401-404
26' (W) x 44' (L) - Rooms 405-407

Chandeliers: Not applicable

Ceiling Height: 13'3" at lowest point, 14'6" at highest point

Power: (1) 20 AMP 120 volts 1 phase

(1) 60 AMP 208 volts 3 phase outlet inside entrance of room

Located in each divisible room:

A/V Panel Lighting Controls Outlets

At the A/V Panels of each room

- (1) RGB Port
- (1) Horizontal/Vertical Port
- (1) Cable TV Port
- (2) Fiber Ports
- (2) Line in Ports
- (2) Mic Lines
- (4) Phone Ports
- (4) CAT 5 Ports

Facilities Guide

Exhibit Hall G

This Exhibit Hall is not subdivided by airwalls and does not share any airwalls with any other space.

Square Feet:	380,000
Dimensions:	Not applicable
Ceiling Height:	13'5" (except in "low hang" areas)
Columns:	(426) 2'6" round spaced 30' apart (center to center)
Power:	Provided by columns
Load-in Door:	(1) 26'1" wide x 13'7" high - for entrance at south end of Hall (roll-up)
	(1) 53'2" wide x 13'7" high - for exit at north end of Hall (slider)
Lighting:	Metal halide, overhead
Floor Load:	Unlimited

Casanova, Marco Polo, and Galileo Ballrooms

Each Ballroom divides by airwalls into fourteen (14) sections.

Dimensions:	79' 6" (W) x 207' 4" (L)
Chandeliers:	Not applicable
Ceiling Height:	11' 4 3/4" at lowest point; 13' 3 3/4" at highest point
Power:	(1) 100 AMP 3 phase

Located in each divisible section of these rooms:

A/V Panel Lighting Controls Outlets

At The A/V Panels of Each Section

- (1) RF
- (1) Portable
- (1) Tele Multi
- (1) Video BNC
- (2) 20 AMP 120 volts (1-floor / 1-wall)
- 2) Ceiling power tracks 50 AMP 3 phase
- (3) MIC Inputs
- (3) Line Inputs
- (5) Internet (RJ45) CAT 5(E) -or- (20) Telephones (RJ11)

LEVEL 2 (CASINO LEVEL)

Exhibit Hall A

This Exhibit Hall is not subdivided by airwalls. Hall A shares an airwall with The Venetian Expo Hall B.

Square Feet:	178,000
Dimensions:	Not applicable
Ceiling Height:	32' 5"
Columns:	(32) 24" square spaced 60' x 90' apart (center to center)
Power:	Dropped from ceiling
Load-in Door:	(1) 50' wide x 20' high
Lighting:	Metal halide, overhead

Exhibit Hall B

This Exhibit Hall is not subdivided by airwalls. Hall B shares an airwall with The Venetian Expo Halls A & C.

Square Feet:	189,000
Dimensions:	Not applicable
Ceiling Height:	32' 5"
Columns:	(32) 24" square spaced 60' x 90' apart (center to center)
Power:	Dropped from ceiling
Load-in Door:	(1) 50' wide x 20' high
Lighting:	Metal halide, overhead

Exhibit Hall C

This Exhibit Hall is not subdivided by airwalls. Hall C shares an airwall with The Venetian Expo Hall B and The Convention Center Hall D.

Square Feet:	188,000
Dimensions:	Not applicable
Ceiling Height:	32' 5"
Columns:	(29) 24" square spaced 60' x 90' apart (center to center)
Power:	Dropped from ceiling
Load-in Door:	(1) 50' wide x 20' high
Lighting:	Metal halide, overhead

Exhibit Hall D

The Exhibit Hall is not subdivided by airwalls. Hall D shares an airwall with The Venetian Expo Hall C.

Dimensions:	414' (L) x 268' (W)
Ceiling Height:	32' 6"
Columns:	(19) 24" square spaced 60' x 90' apart
Power:	(21) 400 AMP 208 volts 3 phase (21) 200 AMP 208 volts 3 phase
Load-in Door:	(1) 19' 11" wide x 16' high
Lighting:	Metal halide, overhead

Facilities Guide

The Venetian Ballroom

The Venetian Ballroom divides by airwalls with twelve (12) sections.
Ten (10) of these sections are directly accessible from public foyers.

Square Footage: 85,000 square feet
Dimensions: 208' 2" (W) x 393' 4" (L)
Ceiling Height: 24' 4" from the lowest ceiling point to the floor
27' 10" from the highest ceiling point to the floor
Chandeliers: (16) each
Clearance: 22' from bottom of chandelier to floor
Sections: The Venetian Ballroom divides into twelve (12) sections
Load-in Doors: One located in The Venetian L and one located in The Venetian K, doors are 12' (W) x 16' (H)
Power: Section A: (1) 200 AMP 208 volts 3 phase,
(1) 400 AMP 208 volts 3 phase
Section B: (2) 200 AMP 208 volts 3 phase,
(1) 400 AMP 208 volts 3 phase
Section C: (2) 200 AMP 208 volts 3 phase,
(1) 400 AMP 208 volts 3 phase
Section D: (1) 200 AMP 208 volts 3 phase
Sections E & F: N/A
Section G: (1) 200 AMP 208 volts 3 phase
Section H: (1) 400 AMP 208 volts 3 phase
Section I: (1) 400 AMP 208 volts 3 phase
Section J: (1) 200 AMP 208 volts 3 phase
Section K: (2) 100 AMP 208 volts 3 phase,
(1) 100 AMP 480 volts 3 phase
Section L: (1) 100 AMP 208 volts 3 phase,
(1) 400 AMP 208 volts 3 phase
(1) 100 AMP 480 volts 3 phase

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

(4) MIC inputs
(4) Line inputs
(2) Video BNC
(1) COM (Clear Com)
(1) RF
(5) Internet (RJ45) CAT 5(E) -or- (20) Telephones (RJ11)
(2) Multi-mode Fiber
(2) Single-mode fiber
(1) 20 AMP 120 volts
(1) 60 AMP 208 volts 3 phase

In the Floor Pockets of Each Ballroom Section

(4) MIC inputs
(1) RF
(2) Internet (RJ45) CAT 5(E) -or- (8) Telephones (RJ11)
(1) 20 AMP 120 volts

The Venetian Foyer Area

The following standard items are included:

Ceiling Height: 18'
Power: (1) 60 AMP 3-phase connection (outside of each room)
(1) 20 AMP connection
(2) A/V Panels

At the A/V Panels

(2) (RJ45) Category 5 certified or the ability to expand each line up to
(4) standard telephone lines
(1) Gang box with (12) RJ11 standard telephone lines

House sound: (4) Mic lines
(2) Coax connections for cable/satellite feed
(2) RF connections for video feed
(1) 60 AMP 3 phase connection (outside of each room)

contents

Facilities Guide

There are no floor pockets in The Venetian foyer area.

The Bellini, Titian, and Veronese Ballrooms

Each ballroom divides by airwalls into fourteen (14) sections.

Dimensions:	80' (W) x 180' (L)
Ceiling Height:	19' 4" from the highest point in the ceiling to the floor 18' from the lowest point in the ceiling to the floor
Chandeliers:	(14) total
Clearance :	15' 6" from the bottom of chandelier to floor 15' 9" from the bottom of the chandelier to the floor in rooms 2001A, 2001B, 2101A, 2101B, 2201A, 2201B, 2301A, 2301B, 2401A, 2401B, 2501A, and 2501B
Power:	(1) 20 AMP connection (2) on each side of the entrance 200 AMP 480 volts can be found in rooms 2106, 2306, and 2506

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

- (3) MIC Inputs
- (2) Line Inputs
- (1) Line Output
- (4) Multi-mode fiber T
- (4) Multi-mode fiber R
- (2) Single-mode fiber TR
- (1) Telephone - 25 lines
- (4) Internet (RJ45) CAT 5(E)
- (2) 20 AMP 120 volts
- (1) 60 AMP 208 volts 3 phase

In the Floor Pocket of Each Ballroom Section

- (2) Internet (RJ45) CAT 5(E)
- (2) MIC Inputs
- (2) Line Outputs
- (1) 20 AMP 120 volts
- (1) RGB - Video
- (2) B&C

In the Ceiling of Each Ballroom Section

- (1) 60 AMP 208 volts 3 phase
- (1) 100 AMP 208 volts 3 phase

Facilities Guide

The Bassano Ballroom 2601-2605

The Ballroom divides by airwalls into five (5) sections.

Dimensions:	39' (W) x 57' 6" (L)
Ceiling Height:	13' 9" from the highest point in the ceiling to the floor 11' 9" from the lowest point to the floor
Chandeliers:	(10) total
Clearance:	9' 3" from bottom of chandelier to floor
Power:	(1) 20 AMP connection (2) on each side of the entrance

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

	(2) (RJ45) Category 5 certified or the ability to expand each line up to (4) (RJ11) standard telephone lines
House sound:	(2) Lines (1) Mic (1) Coax connection for cable/satellite feed (1) RF connection for video feed (1) Mid-level connection for video feed (1) 60 AMP 3 phase connection

The Bassano Ballroom 2701-2710

The Ballroom divides by airwalls into ten (10) sections.

Dimensions:	Maximum 57' 7" (w) x 79' 2" (l)
Ceiling Height:	14' from the highest point in the ceiling to the floor 11' 9" from the lowest point to the floor
Chandeliers:	(5) total
Clearance:	9' 3" from bottom of chandelier to floor
Power:	(1) 20 AMP connection (2) on each side of the entrance

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

	(2) (RJ45) Category 5 certified or the ability to expand each line up to (4) (RJ11) standard telephone lines
House sound:	(1) Mic (1) Mid-level connection for video feed (1) 60 AMP 3 phase connection (2) 20 AMP 120 volts 1 phase connection

The Bassano Ballroom 2801-2802 and 2805-2806

The Ballroom divides by airwalls into 2 (two) section

Dimensions:	18'9" (W) x 19' (L)
Ceiling Height:	14'
Chandeliers:	N/A
Clearance:	6' opening at door
Power:	N/A

contents

Facilities Guide

The Board Rooms Bassano 2606, Bassano 2803, and Bassano 2804

Bassano 2606 is set U-shape for 15 guests.

Bassano 2803 and 2804 are set conference style for 16 guests.

The furniture within these rooms is permanent and cannot be moved or removed for any reason.

The above mentioned Board Rooms are not to be used as storerooms or general breakout rooms.

Power: (2) 20 AMP 120 volts 1 Phase Connection

contents

LEVEL 3 (GRAND CANAL SHOPPES LEVEL)

The Lido, Murano, and San Polo Ballrooms

Each ballroom divides by airwalls into fourteen (14) sections.

Dimensions:	80' (W) x 180' (L)
Ceiling Height:	19' 6" from the highest point in the ceiling to the floor
	18' from the lowest point in the ceiling to the floor
Chandeliers:	(14) total
Clearance:	15' 6" from the bottom of chandelier to floor 15' 9" from the bottom of the chandelier to the floor in rooms 3001A, 3001B, 3101A, 3101B, 3201A, 3201B, 3301A, 3301B, 3401A, 3401B, 3501A, and 3501B
Power:	(1) 20 AMP connection (2) on each side of the entrance
	200 AMP 480 volts can be found in rooms 3101B, 3301B, and 3601B
	200 AMP 480 volts can be found in rooms 3101B, 3301B, and 3601B

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

- (1) MIC Input
- (1) Line Output
- (4) Multi-mode fiber T
- (4) Multi-mode fiber R
- (2) Single-mode fiber TR
- (1) Telephone - 25 lines
- (4) Internet (RJ45) CAT 5(E)
- (2) 20 AMP 120 volts

In the Floor Pocket of Each Ballroom Section

- (2) Internet (RJ45) CAT 5(E)
- (2) MIC Inputs
- (2) Line Outputs
- (1) 20 AMP 120 volts
- (1) RGB - Video
- (2) B&C

In the Ceiling of Each Ballroom Section

- (1) 60 AMP 208 volts 3 phase
- (1) 100 AMP 208 volts 3 phase

Facilities Guide

The Toscana Ballrooms 3601-3610 and 3701-3710

Each Ballroom divides by airwalls into ten (10) sections.

Dimensions:	Maximum 57'7" (W) x 79'2" (L)
Ceiling Height:	13' 9" from the highest point in the ceiling to the floor 11' 9" from the lowest point to the floor
Chandeliers:	(5) total
Clearance:	9' 3" from bottom of chandelier to floor
Power:	(1) 20 AMP connection (2) on each side of the entrance (1) 60 AMP 208 volts 3 phase

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

	(2) (RJ45) Category 5 certified or the ability to expand each line up to
	(4) (RJ11) standard telephone lines
House sound:	(1) Mic (1) Coax connection for cable/satellite feed (1) RF connection for video feed (1) Mid-level connection for video feed (1) 60 AMP 3 phase connection (2) 20 AMP 120 volts 1 phase

The Toscana Ballroom 3801-3802 and 3805-3806

The Ballroom divides by airwalls into 2 (two) section

Dimensions:	18'9" (W) x 19' (L)
Ceiling Height:	14'
Chandeliers:	N/A
Clearance:	6' opening at door
Power:	N/A

The Board Rooms Toscana 3803 and 3804

Board Rooms are set conference style for 16 guests.

The furniture within these rooms is permanent and cannot be moved or removed for any reason.

The above mentioned Board Rooms are not to be used as storerooms or general breakout rooms.

Power:	(2) 20 AMP 120 volts 1 phase
Television:	Sharp 80" High Definition. HDMI Capable

LEVEL 4

The Delfino, Lando, and Marcello Ballrooms

Each ballroom divides by airwalls into fourteen (14) sections.

Dimensions:	80' (W) x 180' (L)
Ceiling Height:	19' 6" from the highest point in the ceiling to the floor 18' from the lowest point in the ceiling to the floor
Chandeliers:	(14) total
Clearance:	15' 3" from the bottom of chandelier to floor 15' 9" from the bottom of the chandelier to the floor in rooms 4001A, 4001B, 4101A, 4101B, 4201A, 4201B, 4301A, 4301B, 4401A, 4401B, 4501A, and 4501B
Power:	(1) 20 AMP connection (2) on each side of the entrance (1) 60 AMP 208 volts 3 phase (1) 100 AMP 208 volts 3 phase (1) 200 AMP 480 volts can be found in rooms 4106, 4306, and 4506

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

- (3) MIC Inputs
- (2) Line Inputs
- (1) Line Output
- (4) Multi-mode fiber T
- (4) Multi-mode fiber R
- (2) Single-mode fiber TR
- (1) Telephone - 25 lines
- (4) Internet (RJ45) CAT 5(E)
- (1) 20 AMP 120 volts
- (1) 60 AMP 208 volts 3 phase
- (1) 100 AMP 208 volts 3 phase

In the Floor Pocket of Each Ballroom Section

- (2) Internet (RJ45) CAT 5(E)
- (2) MIC Inputs
- (2) Line Outputs
- (1) 20 AMP 120 volts
- (1) RGB - Video
- (2) B&C

Facilities Guide

The Zeno Ballrooms 4601-4610 and 4701-4710

Each Ballroom divides by airwalls into ten (10) sections.

Dimensions:	Maximum 57'7" (W) x 79'2" (L)
Ceiling Height:	13' 9" from the highest point in the ceiling to the floor 11' 9" from the lowest point to the floor
Chandeliers:	(5) total
Clearance:	9'3" from bottom of chandelier to floor
Power:	(1) 20 AMP connection (2) on each side of the entrance (1) 60 AMP 208 volts 3 phase

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Each Section

	(2) (RJ45) Category 5 certified or the ability to expand each line up to
	(4) (RJ11) standard telephone lines
House sound:	(1) Mic (1) Mid-level connection for video feed (1) 60 AMP 208 volts 3 phase

The Zeno Ballroom 4801-4802 and 4805-4806

The Ballroom divides by airwalls into 2 (two) section

Dimensions:	18'9" (W) x 19' (L)
Ceiling Height:	14'
Chandeliers:	N/A
Clearance:	6' opening at door
Power:	N/A

The Board Rooms Zeno 4803 and 4804

Board Rooms are set conference style for 16 people.

The furniture within these rooms is permanent and cannot be moved or removed for any reason.

The above mentioned Board Rooms are not to be used as storerooms or general breakout rooms.

Power:	(2) 20 AMP 120 volts 1 phase
Television:	Sharp 80" High Definition. HDMI Capable

contents

LEVEL 5

The Palazzo Ballroom

The ballroom divides by airwalls into sixteen (16) sections.

Square footage:	75,000 square feet
Dimensions:	368' (L) x 196' (W)
Ceiling Height:	28' from the highest point in the ceiling to the floor 25' from the lowest point in the ceiling to the floor
Chandeliers:	(16) Large (4) Small
Clearance: to the floor	20' 11" from the bottom of the chandelier to the floor
Power:	(1) 100 AMP 208 volts 3 phase ceiling track (2) 20 AMP 120 volts (1) 400 AMP 208 volts 3 phase (1) 100 AMP 208 volts 3 phase

Located in each divisible section of these rooms:

A/V Panel House Phones Lighting Controls

At the A/V Panels of Sections A, B, C, D, E, H, I, L, M, N, O, and P

- (1) Mic Input
- (2) Line Inputs
- (4) Dry Pair
- (4) CAT 5E - phone or Internet
- (2) Multi-mode fiber
- (16) Phones
- (1) Single-mode fiber

In the Floor Pockets of Sections A, B, C, D, E, H, I, L, M, N, O, and P

- (6) XLR Dry Lines
- (2) Single-mode fiber
- (4) CAT 5E - phone or Internet
- (1) 20 AMP 120 volts
- (4) Multi-mode fiber

In the Floor Pockets of Sections F, G, J, and K

- (1) Mic Input
- (2) Single-mode fiber
- (2) Line Input
- (4) CAT 5E - phone or Internet
- (4) XLR Dry Lines
- (1) 20 AMP 120 volts
- (4) Multi-mode fiber

Outside Sections A, B, C, D, E, H, I, L, M, N, O, and P

- (4) CAT 5E - phone or Internet
- (2) Single-mode fiber
- (2) Multi-mode fiber
- (1) 20 AMP 120 volts

POOL DECKS

The Palazzo Pool Decks*

Rotunda

50 max occ

Pools 1-3

540 max occ

Pool 1-4

900 max occ

Pool 6

360 max occ

Total assembly occupancy for The Palazzo pools (not including flow) = 3,060 persons

(Based on square footage and available exits)

The Venetian Pool Decks*

Pool 1 & 2

724 max occ

Pool 3 & 4

910 max occ

Pool 4

342 max occ

Total assembly occupancy for The Venetian pools (not including flow) = 1,840 persons (Based on square footage and available exits)

The Palazzo and The Venetian Pool Decks*

Entire Pool Deck

4,900 max occ

Total assembly occupancy for The Palazzo and The Venetian pools (not including flow) = 4,900 persons (Based on square footage and available exits)

The pool deck floor load limits is 100 pounds per square foot. Any exhibit, display, or equipment is not permitted. You are responsible for contacting "The Venetian Resort Las Vegas" with any potential weight concerns.

*Is the specific pool area and maximum occupant loads based on available exits, areas of refuge, and square footage.



THE VENETIAN® RESORT
LAS VEGAS

The Venetian® and other trademarks are used under license.